

六角棒 (SUS304,303)

サイズ	kg/m	304				303			
		長さ→ 2.0	2.5	3.0	4.0	2.0	2.1	3.0	4.0
4	0.110	●				●			
5	0.172	●				●			
5.5	0.208					●			
6	0.247	●				●			
7	0.337			●		●	●		
8	0.440			●			●		
9	0.556				●			●	
10	0.687	○		○	○			○	○
11	0.831				○				○
12	0.989	○		○	○			○	○
13	1.16			○	○			○	○
14	1.35	○	○	○	○			○	○
17	1.98	○	○	○	○	○		○	○
19	2.48			○	○			○	○
21	3.03				○				○
22	3.32				○				○
23	3.63			○	○				○
24	3.96			○	○				○
26	4.64				○				○
27	5.01				○				○
29	5.78				○				○
30	6.18				○				○
32	7.03	○			○				○
35	8.41				○				○
36	8.90				○				○
38	9.92				○				○
41	11.5				○				○
46	14.5				○				○
50	17.2				○				○
54	20.0				○				○
55	20.8				○				○

55以下はスキンパス仕上げ

※ 303 : 4, 5, 5.5, 6, 7は303Cuになります。


六角が取れる丸棒寸法

丸棒の直径 = 六角の対辺 × 1.156

六角棒の1M重量

SUS-304,303 = 0.00686 × H × H

SUS-316,316L = 0.00691 × H × H



○ 在庫品切断可 ● 在庫品寸法切断不可

酸洗六角棒 (SUS304,303)

サイズ	kg/m	304	303
58	23.1	○	
60	24.7	○	○
63	27.2	○	
65	29.0	○	
67	30.8	○	
70	33.6	○	
75	38.6	○	
80	43.9	○	
85	49.6	○	
90	55.6	○	

定尺品長さ3000L~4000L

[六角棒平径寸法公差]

サイズ		h12	h13
3~6	+0,	-0.12	-0.18
7~10	+0,	-0.15	-0.22
11~17	+0,	-0.18	-0.27
19~30	+0,	-0.21	-0.33
32~50	+0,	-0.25	-0.39
54~80	+0,	-0.30	-0.46
85~	+0,	-0.35	-0.54

スキンパス仕上げ 12級 (h12)

酸洗仕上げ 13級 (h13)