

# アングル (SUS304) 熱間圧延品

比重 7.93

サイズ	kg/m	304	
		4M	6M
3 × 20 × 20	.894	○	
3 × 25 × 25	1.13	○	
3 × 30 × 30	1.37	△	○
3 × 35 × 35	1.61	△	○
3 × 40 × 40	1.85	△	○
3 × 50 × 50	2.37	△	○
4 × 30 × 30	1.77		○
4 × 35 × 35	2.10		○
4 × 40 × 40	2.41	△	○
4 × 50 × 50	3.09	△	○
5 × 30 × 30	2.18		○
5 × 40 × 40	2.98	△	○
5 × 45 × 45	3.41		○
5 × 50 × 50	3.81	△	○
5 × 60 × 60	4.60		○
5 × 65 × 65	5.05		○
5 × 70 × 70	5.45		○
5 × 75 × 75	5.84		○
6 × 30 × 30	2.54		○
6 × 35 × 35	3.03		○
6 × 40 × 40	3.50		○
6 × 45 × 45	4.01		○
6 × 50 × 50	4.48	△	○
6 × 60 × 60	5.44		○
6 × 65 × 65	5.97	△	○
6 × 75 × 75	6.92	△	○
6 × 80 × 80	7.40		○
6 × 90 × 90	8.37		○
6 × 100 × 100	9.32	△	○
7 × 70 × 70	7.42		○
8 × 65 × 65	7.74		○
8 × 75 × 75	9.01		○
8 × 80 × 80	9.64		○
8 × 90 × 90	11.0		○
8 × 100 × 100	12.2		○
9 × 50 × 50	6.44		○
9 × 60 × 60	7.87		○
9 × 65 × 65	8.64		○
9 × 70 × 70	9.35		○
9 × 75 × 75	10.1	△	○
9 × 90 × 90	12.3	△	○
9 × 100 × 100	13.7		○
9 × 125 × 125	17.2		○
9 × 150 × 150	20.8		○

サイズ	kg/m	304	
		4M	6M
10 × 60 × 60	8.68		○
10 × 100 × 100	15.1	△	○
12 × 100 × 100	17.9		○
12 × 125 × 125	22.6		○
12 × 130 × 130	23.6		○
12 × 150 × 150	27.5		○
15 × 125 × 125	28.0		○
15 × 150 × 150	33.9		○

## 不等辺アングル (SUS304) 熱間圧延品

サイズ	kg/m	304	
		4M	6M
★ 4 × 45 × 30	2.27		○
★ 6 × 50 × 30	3.57		○
★ 6 × 65 × 50	5.28		○
6 × 75 × 50	5.73		○
★ 6 × 75 × 65	6.47		○
6 × 100 × 75	8.13		○
6 × 125 × 75	9.32		○
7 × 75 × 50	6.58		○
★ 7 × 100 × 75	9.45		○
★ 9 × 75 × 50	8.33		○
★ 9 × 90 × 75	11.2		○
9 × 100 × 75	11.9		○
9 × 125 × 75	13.7		○
9 × 150 × 90	16.5		○
12 × 150 × 90	21.7		○

★ …片辺切断品

## チャンネル (SUS304) 熱間圧延品

サイズ	kg/m	304	
		4M	6M
3 × 20 × 40	1.80		○
3 × 25 × 50	2.28		○
★ 3 × 40 × 80	3.72		○
★ 3 × 50 × 100	4.75		○
4 × 50 × 100	6.18	△	○
5 × 40 × 80	5.98	△	○
5 × 50 × 100	7.64	△	○
6 × 50 × 100	9.01	△	○
★ 6 × 60 × 120	10.9		○
6 × 65 × 130	12.0	△	○
6 × 75 × 150	13.9	△	○
★ 6 × 100 × 200	18.7		○
★ 8 × 100 × 200	24.6		○
9 × 75 × 150	20.2	△	○
10 × 100 × 200	30.3	△	○

★ …溶接チャンネル

納入状態 ST (固溶化熱処理)  
納入硬さHB187以下

○ 在庫品切断可  
△ 取寄品切断可